

5614 UR XX

Subway - Washdown WC, rimless - 1.6/0.8 gpf (6/3 lpf)

Features

- Washdown WC, rimless
- 14 5/8" x 22" (370 x 560 mm)
- 1.6/0.8 gpf (6/3 lpf)
- Washdown model
- Rear outlet
- Concealed trapway
- D-shape bowl

The bowl is to be used with In-wall tank/carrier from TOTO (WT152M DUOFIT IN-WALL TANK SYSTEM) or Geberit (# 111.335.00.5) to satisfy EPA WaterSense.

Optional CeramicPlus - CeramicPlus is a particularly easy-care and dirt-repellent surface. With ceramicplus water immediately forms droplets that simply flow off the surface, taking the dissolved dirt and limescale with them.



Codes / Standard applicable

- ADA compliant
- EPA - Watersense
- Meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14
- Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others
- Certifications: IAPMO(cUPC), State of Massachusetts
- Code Compliance: UPC, IPC, NSPC, NPC Canada and others



Colors - XX

- 01 = White Alpin
- R1 = White Alpin Ceramicplus

Product Specification

This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22" (560mm) x 14 5/8" (370mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 5614UR

Components

Included	
5614 UR XX	Washdown WC, rimless, Incl. fastening set "SupraFix 2.0"
Required	
9M68 U1 01	WC-seat and cover, Hinges in stainless steel, With quick-release and softclosing hinges
Optional	
9M68 U0 01	WC-seat and cover, Hinges in stainless steel
9M78 U1 01	WC-seat and cover, Hinges in stainless steel, With quick-release and softclosing hinges
9M78 U6 01	WC-seat and cover, Hinges in stainless steel

Installation Notes

Install this product according to the installation manual.

Technical Information

Water use	1.6/0.8 gpf (6/3 lpf)
Material	Vitreous china
Warranty	One year limited warranty
Min Water pressure	8 psi
Water surface	4" x 5" (100 x 130 mm)
Trap diameter	2" (50mm)
Trap seal	2 3/8" (60mm)
Minimum rough-in	7" (180 mm) rough-in
Outlet	Rear outlet
Shipping dimensions	17 1/8" x 25 9/16" x 18"

Technical Drawing

